



SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: DERMA SEAL	Product Use: Concrete Masonry Sealer
Manufacturer's Name: The Concure Group	Emergency Telephone: 610-864-8502
Address: 18 Campus Blvd, Suite 100 Newtown Square, PA 19073	Telephone Number: 800-636-6550
Date Prepared: DECEMBER 2014	Date Updated: January 2, 2017

SECTION 2: HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION



Skin Irritant 2 H315 Causes skin irritation.
 Eye Irritant 2 H318 Causes serious eye irritation.
 Skin Sensitization 1 H317 May cause an allergic skin reaction

LABEL ELEMENTS

Hazard Pictogram:



Signal Word: Danger

Hazard Statements: Irritant.

- H315 – Causes skin irritation.
- H317 – May cause an allergic skin reaction.
- H317 – Causes serious eye irritation.
- H332 – Harmful if inhaled.
- H335 – May cause respiratory irritation.

Precautionary Statements:

- P101 – If medical advice is needed, have product container or label at hand.
- P102 – Keep out of reach of children.
- P202 – Do not handle until all safety precautions have been read and understood.
- P233 – Keep container tightly closed.
- P234 – Keep only in original container.
- P260 – Do not breathe dust/fume/gas/mist/vapors/spray.
- P262 – Do not get in eyes, on skin, or on clothing.
- P264 – Wash thoroughly with plenty of water immediately after handling.
- P270 – Do not eat, drink or smoke when using this product.
- P271 – Use only outdoors or in a well-ventilated area.
- P273 – Avoid release to the environment and drains.
- P280 – Wear protective gloves/protective clothing/eye protection/face protection.
- P284 – Wear respiratory protection.
- P314 – Get medical advice/attention if you feel unwell.



P391 – Collect spillage.
 P402 + P404 – Store in a dry place. Store in a closed container.
 P403 + P233 – Store in a well-ventilated place. Keep container tightly closed.
 P405 – Store locked up.
 P501 – Dispose of contents and container as hazardous waste in accordance with all local, regional, national and international regulations.

ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.
 10.0 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

MATERIAL OR INGREDIENT	CAS #	WT. %
Alkoxy silanes + siloxane	Mixture	< 20 %
3-Aminopropyltriethoxysilane	919-30-2	< 0.5

Exact composition percentage/concentration has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: FIRST-AID MEASURES

DESCRIPTION OF THE FIRST AID MEASURE

P301 + P310 + P330 + P331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.
 P302 + P352 + P361 – IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get immediate medical advice/attention.
 P304 + P311 + P340 + P341 + P342 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
 P305 + P313 + P337 + P338 + P351 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 P306 + P360 – IF ON CLOTHING: Immediately rinse contaminated clothing and skin with plenty of water before removing clothes.
 P314 – Get medical advice/attention if you feel unwell.

IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: May cause moderate eye irritation.
Skin: Brief contact may cause moderate skin irritation with local redness. Prolonged skin contact is unlikely to result in absorption of harmful amounts. Has caused allergic skin reactions in humans.
Inhalation: At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material, mist or aerosols may cause respiratory irritation.
Ingestion: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.
Chronic Health Hazard: This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately. Corticosteroid cream has been effective in treating skin irritation.
Specific Treatments: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. In case of accident or if you feel unwell, seek medical advice immediately (provide label or SDS).

SECTION 5 – FIRE-FIGHTING MEASURES

FLAMMABILITY

Flammability: Not flammable by WHMIS/OSHA criteria.

EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use extinguishing media appropriate for the surrounding fire. Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:

During a fire, smoke may contain combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: silicon dioxide, formaldehyde, carbon dioxide, carbon monoxide and incompletely burnt hydrocarbons. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Firefighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Contain fire water run-off if possible. Firewater run-off may cause environmental damage.

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective firefighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during firefighting operations. If contact is likely, change to full chemical resistant firefighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Open enclosed spaces to outside atmosphere. Evacuate personnel to safe areas and do not approach spilled product. If possible, stop flow of product.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN - UP

Methods for Containment: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Prevent material from entering surface waters, drains or sewers and soil. Close leak, if possible, without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

Methods for Cleaning-Up: Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth

and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapors. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Handling:

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release ethanol. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Observe local/state/federal regulations. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in air-tight labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Store in a temperature-controlled area between 5°C (40°F) and 30°C (90°F).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

Exposure Guidelines

Ingredient	Occupational Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Alkoxy silanes + siloxane	Not available.	Not available.
Ethanol	1,900 mg/m ³	1,000 ppm

EXPOSURE CONTROLS

Engineering Controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Wear approved face (face shield) protection or properly fitted splash-proof chemical safety goggles.

Skin Protection:

Hand Protection: Wear suitable impervious Neoprene gloves, PVC disposable gloves, or Nitrile rubber gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved Mist Respirator or filtering facepiece. Respirators should be selected by and used under the direction of a trained health and safety professional following OSHA and ANSI requirement standards.

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Milky White / Off-White
Odor	Faint
pH	5.0 – 8.0
Melting Point/Freezing Point	1°C (34°F)
Initial Boiling Point and Boiling Range	100°C (212°F)
Flash Point	> 100°C (> 212°F)
Evaporation Rate	Not Available
Flammability	NFPA Hazard Class (Comb./Flam. Liquid) IIIB
Lower Flammability/Explosive Limit	Not Available
Upper Flammability/Explosive Limit	Not Available
Vapor Pressure	23 hPa / 20°C (68°F)
Vapor Density	Not Available
Relative Density/Specific Gravity	0.95 to 1.00
Solubility	Miscible
Partition coefficient: n-octanol/water	Not Available
Auto-Ignition Temperature	Not Available
Decomposition Temperature	Not Available
Oxidizing Properties	No
Explosive Properties	Explosion Limits: Explosion limits for released ethanol: 3.5-15% (V)

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY
If stored and handled in accordance with standard industrial practices no hazardous reactions are known.
CHEMICAL STABILITY
Stable under normal storage conditions and conditions of normal use.
POSSIBILITY OF HAZARDOUS REACTIONS
Hazardous polymerization will not occur.
CONDITIONS TO AVOID
Heat, open flames, and other sources of ignition.
INCOMPATIBLE MATERIALS
Reacts with: basic substances and acids. Reaction causes the formation of: ethanol.
HAZARDOUS DECOMPOSITION PRODUCTS
By hydrolysis: ethanol. The following applies for the silicone content of the substance: Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: TOXICOLOGICAL INFORMATION



INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: May cause serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: Symptoms may include redness, edema, drying, defatting and cracking of the skin. Do not allow continuous, prolonged contact with skin. May cause sensitization by skin contact.

Inhalation: May cause respiratory tract irritation. Inhalation of respirable aerosol should be avoided.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Acute Toxicity:

Ingredient	LC50	LD50
Alkoxy silanes + siloxane	Not available.	Oral > 2000 mg/kg, rat
Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
Not available.	Not available.	Not available.
Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65) *	
Alkoxy silanes + siloxane	Not listed.	

Substances listed in the Sections 15 and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or they are inextricably bound in the product. Specific chemical identities and percentages (concentration) of the composition may have been withheld as a trade secret.

(* See Section 15)

DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT-TERM AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: May cause skin irritation.

Serious Eye Damage/Irritation: May cause serious eye irritation.

Respiratory Sensitization: Classification criteria are not available.

Skin Sensitization: May cause an allergic skin reaction.

STOT-Single Exposure: May cause respiratory irritation.

Chronic Health Effects:

Carcinogenicity: Not available.

Germ Cell Mutagenicity: Not available.

Reproductive Toxicity:

Developmental: Not available.

Teratogenicity: Not available.

Embryotoxicity: Not available.

Fertility: Not available.

STOT-Repeated Exposure: Not available.

Aspiration Hazard: Classification criteria are not available.

Toxicologically Synergistic Materials: Not available.

Other Information: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: Hydrolysis product / impurity: Ethanol (64-17-5) is readily absorbed at all exposure routes. Ethanol may cause irritation of eyes and mucosa, trigger dysfunction of the central nervous system and cause nausea as well as dizziness. Chronic exposure to high amounts of ethanol may cause damage to liver and central nervous system.



SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY

Acute/Chronic Toxicity: According to current knowledge adverse effects on water purification plants are not expected.

PERSISTENCE AND DEGRADABILITY

Contact with water liberates ethanol and silanol- and/or siloxanol-compounds. Silicone content: biologically not degradable. Elimination by adsorption to activated sludge. The hydrolysis product (Ethanol) is readily biologically degradable.

BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

MOBILITY IN SOIL

Not available.

OTHER ADVERSE EFFECTS

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other Disposal Recommendations: Not available

SECTION 14: TRANSPORT INFORMATION

UN NUMBER

Not regulated.

UN PROPER SHIPPING NAME

Not applicable.

TRANSPORT HAZARD CLASS (ES)

Not applicable.

ENVIRONMENTAL HAZARDS

Not available.

SPECIAL PRECAUTIONS

Do not handle until all safety precautions have been read and understood.

SECTION 15: REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Alkoxy silanes + siloxane	None.	None.	None.	None.

California Proposition 65 Carcinogens: This product does not contain chemicals known to the state of California to cause cancer.

California Proposition 65 Reproductive Toxins:

CAS No.	Chemical	Upper limit wt. %
67-56-1	Methanol	<=0.0029


WHMIS Classification(s):

- Class D2A - Chronic Toxic Effects
- Class D2B - Skin/Eye Irritant

TSCA:

Ingredient	USA TSCA LISTED
Alkoxy silanes + siloxane	Yes.

WHMIS Hazard Symbols:



NFPA National Fire Protection Association	
Health:	2
Fire:	1
Reactivity:	0

HMIS-Hazardous Materials Identification System	
Health:	2*
Fire:	1
Reactivity:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

*** SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:**

- CP65** **California Proposition 65**
- OSHA (O)** **Occupational Safety and Health Administration.**
- ACGIH (G)** **American Conference of Governmental Industrial Hygienists.**
 - A1 - Confirmed human carcinogen.
 - A2 - Suspected human carcinogen.
 - A3 - Animal carcinogen.
 - A4 - Not classifiable as a human carcinogen.
 - A5 - Not suspected as a human carcinogen.
- IARC (I)** **International Agency for Research on Cancer.**
 - 1 - The agent (mixture) is carcinogenic to humans.
 - 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
 - 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
 - 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
 - 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
- NTP (N)** **National Toxicology Program.**
 - 1 - Known to be carcinogens.
 - 2 - Reasonably anticipated to be carcinogens.

SECTION 16: OTHER INFORMATION

Date of Preparation:	December 22, 2014
Version:	1701
Revision Date:	January 2, 2017

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It



The
Concure
Group

SAFETY DATA SHEET

DERMASEAL

may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.